

PCI-7841 / cPCI-7841

Dual-port Isolated CAN Interface Cards



Introduction

The PCI-7841/cPCI-7841 is a Controller Area Network (CAN) interface card. It supports a dual-port CAN interface that can run independently or bridged together. The built-in CAN controller is a Philips SJA1000, which provides bus arbitration and error detection with auto correction and re-transmission functionality.

Controller Area Network

The CAN (Controller Area Network), a serial bus system originally developed by Bosch for use in automobiles, is increasingly used for industry automation. Its multi-master protocol, real-time capability, error correction and high noise immunity makes it especially suited for intelligent I/O devices control network.

Features

- Two independent CAN network operation
- Up to 1 Mbps programmable transfer rate
- 16 MHz CAN controller frequency
- 2500 VRMS isolation protection
- Direct memory mapping to the CAN controllers
- Powerful master interface for CAN bus protocols
- PCI bus plug-and-play
- Supports Windows® 2000/XP and Linux operation systems
- Only supports CompactPCI interface 5V (I/O)

Software Support

- **PCI-7841**
 - Dos driver
 - Windows® NT/2000/XP/7
 - Linux driver
- **cPCI-7841**
 - Dos driver
 - Windows® NT/2000/XP/7
 - Linux driver

Specifications

| | |
|-------------------------|---|
| ■ Ports 2 | CAN channels (V2.0 A, B) |
| ■ CAN Controller | SJA1000 |
| ■ CAN Transceiver | 82C250/251 |
| ■ Isolation Voltage | 2500 VRMS |
| ■ Connectors | Dual DB9 male connectors for PCI-7841 5-pin screw terminal for cPCI-7841 |
| ■ Operating Temperature | 0 to +60 °C |
| ■ Storage Temperature | -20 °C to +80 °C |
| ■ Humidity | 5 to 95%, non-condensing |
| ■ Power Consumption | +5 V @ 400 mA typical, @ 900 mA max. |
| ■ Dimensions | PCI-7841: 132 mm x 107 mm (H x L) cPCI-7841: 100 mm x 160 mm (H x L) |

Ordering Information

- **PCI-7841**
Dual-port isolated CAN interface card
- **cPCI-7841**
Dual-port isolated CAN interface card in 3U CompactPCI form factor
- **cPCI-7841R**
Dual-port isolated CAN interface card in 3U CompactPCI form factor with rear I/O support