

W-White

RACK-220GB B-Black

Features

- RoHS compliant design
- Two USB ports on the front panel
- Two 8 cm cooling fans with replaceable fan filter
- One 5.25" and one 3.5" drive bays
- One 3.5" internal hard drive bay
- · Lockable door prevents unauthorized access

Specifications


-	
♦ Construction	Heavy duty metal
♦ SBC Form Factor	Full-size, slot CPU card
♦ Drive Bays	1 x 5.25" 1 x 3.5" 1 x 3.5" HDD (internal)
♦ Cooling Fans	2 x 8 cm
♦ I/O Ports	2 x USB
♦ Expansion Slots	6 slots
♦ Indicators	Power, HDD
♦ Buttons	Power switch, reset button
Operating Temperature	0°C ~ 50°C
Operating Humidity	10% ~ 90%
♦ Color	W: White/B: Black
♦ Weight (Net/Gross)	8.2 kg/12.4 kg
♦ Dimensions (DxWxH)	448 mm x 431 mm x 88 mm

Ordering Information

Part No.	Description
RACK-220G C /A130B	2U 6-slot full-size rackmount chassis for PICMG 1.0 SBC, (black/white), 2 x 8 cm fan, with ACE-A130B-R10 (300W ATX model), RoHS
RACK-220G C ATX/A130B	2U microATX motherboard rackmount chassis, (black/ white), 2 x 8 cm fan, with ACE-A130B-R10 (300W ATX model), RoHS

C Color Code: B-Black W-White

Dimensions (Unit: mm)



Selection Guide

Model No.	SBC Type	PSU Type	Color Options	
RACK-220G C	PICMG 1.0	PS/2	Black/White	V
RACK-220G C ATX	microATX MB	PS/2	Black/White	С

Backplane Options

Model No.	SPC Turne	PCI	ISA	PCle			PSU
Model No.	SBC Type			x1	x4	x16	Connector
PCI-5SDA-RS	PICMG 1.0	L2+R2	0	0	0	0	AT/ATX
PCI-5SD5-RS	PICMG 1.0	L2+R2	0	0	0	0	AT
PCI-5SD6-RS	PICMG 1.0	L2+R2	0	0	0	0	ATX
PCI-6SD-RS	PICMG 1.0	L1+R1	L1+R1	0	0	0	ATX

Power Supply Options

Туре	Model No.	Watt	
AT	ACE-925AP-U-RS	250W	
	ACE-935AL-RS	300W	
ATX	ACE-A130B-R10	300W	P
	ACE-A140A-S-R11	400W	

RACK-220G supports single PS/2 PSU. For more IEI PSU models, please refer to section 5 or visit www.ieiworld.com.



Industria Computir





Industria vsten

