

Datasheet

M.2 (S80) 3TG6-P series

- SATA III solution for industrial field
- High IOPS
- Excellent random performance
- End to end data path protection
- iData Guard for abnormal power failure
- Compatible with M.2 2280-D2-B-M standard



Introduction


Innodisk M.2 (S80) 3TG6-P is SATA III 6Gb/s solid state disk, which delivers excellent performance, especially in random data transfer rate, and which offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. M.2 (S80) 3TG6-P not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.

Innodisk M.2 (S80) 3TG6-P is designed for industrial field, and supports several standard features, including TRIM, NCQ, and S.M.A.R.T. In addition, Innodisk's exclusive industrial-oriented firmware provides a flexible customization service, making it perfect for a variety of industrial applications.

M.2 (S80)

3TG6-P series

Diagram



Specifications

Interface	SATA III
Flash Type	3D TLC
P/E cycle	3,000
Capacity	128GB~256GB
Max. Channels	4
Sequential R/W (MB/sec, max.)	560/250
Max. Power Consumption	1.87W(566.6mA x 3.3V)
Thermal Sensor	✓
External DRAM buffer	✓
H/W Write Protect	Optional
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	22.0 X 80.0 X 3.8mm (Max)
Environment	Vibration: 20G @ 7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

© 2020 Innodisk Corporation.
All right reserved. Specifications are
subject to change without
prior notice.

20200305

Operation Temp.	128GB	256GB
Standard Grade (0°C ~ +70°C)	DGM28- A28M71EC1QL	DGM28- B56M71EC1QL

Distributore Autorizzato per l'Italia:

Contradata Milano S.r.l.

Via Solferino 12, 20900 Monza (MB) - Italy

Tel: (+39) 039-230.14.92 | Email: info@contradata.it



www.contradata.it

innodisk