


Datasheet

M.2 (S42) 3TG6-P series

- SATA III solution for industrial field
- Exclusive L³ architecture
- AES-256bits encryption
- Excellent random performance
- Supports TRIM/NCQ/SMART
- Built in iData Guard
- Compatible with M.2 2242-D2-B-M standard
- Designed with hardware LDPC ECC engine



Introduction


Innodisk M.2 (S42) 3TG6-P is SATA III 6.0 Gb/s flash based disk, which delivers excellent performance, especially in random data transfer rate, and which offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. M.2 (S42) 3TG6-P not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.

Innodisk M.2 (S42) 3TG6-P is designed for industrial field, and supports several standard features, including TRIM, NCQ, and S.M.A.R.T. In addition, Innodisk's exclusive industrial-oriented firmware provides a flexible customization service, making it perfect for a variety of industrial applications.

M.2 (S42)

3TG6-P series

Diagram



Specifications

Interface	SATA III
Flash Type	3D TLC
P/E cycle	3,000
Capacity	128GB~1TB
Max. Channels	4
Sequential R/W (MB/sec, max.)	560/510
Max. Power Consumption	2.58W (780mA $\times$ 3.3V)
Thermal Sensor	✓
External DRAM buffer	✓
H/W Write Protect	-
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	22.0 X 42.0 X 3.5 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

Ordering Information

Operation Temp.	128GB	256GB	512GB	1TB
Standard Grade (0°C ~ +70°C)	DGM24-A28M71ECAQF	DGM24-B56M71ECAQF	DGM24-C12M71ECAQF *DGM24-C12M71GCAQL	*DGM24-01TM71GCAQF
Industrial Grade (-40°C ~ +85°C)	DGM24-A28M71EWAQF	DGM24-B56M71EWAQF	DGM24-C12M71EWAQF	

*96 Layer 3D TLC


innodisk

Distributore Autorizzato per l'Italia:

Contradata Milano S.r.l.

Via Solferino 12, 20900 Monza (MB) - Italy

Tel: (+39) 039-230.14.92 | Email: info@contradata.it



©2020 Innodisk

www.contradata.it

© 2020 Innodisk Corporation.
All right reserved. Specifications are
subject to change without
prior notice.

20190225