

Contact us for more information about the InnoAGE mSATA 3TI7.

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the industrial/embedded, aerospace and defense, and cloud computing industries.



Specifications

Interface	SATA III
Flash Type	3D TLC
Capacity	32GB~ 256GB
Flash Endurance	3,000 P/E cycles
Max. Channels	4
Sequential R/W (MB/sec, max.)*	560 / 330 MB/s
4KB Random (QD32) R/W (IOPS)**	79,000/ 64,000
Max. Power Consumption	1.5W
Thermal Sensor	
ATA Security	
S.M.A.R.T.	
Dimension (WxLxH)	29.85 X 50.8 X 3.7 mm
Environment	Vibration: 20G @ 7~ 2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C to +95°C MTBF: 3 million hours
* Performance based on CrystalDiskMark 5.01 with file size 1000MB	

Quick Erase	Security Erase	Destroy	Recovery	iAnalyzer	S.M.A.R.T.
V	V	V	V	V	V
iData Guard	iPower Guard	ATA Security	TRIM	256-bit AES	
V	V	V	V	V	

Ordering Information

Capacity	Standard Temperature (0°C~70°C)	Industrial Temperature (-40°C~85°C)
32GB	DTMSR-32GDK1% C *SL10G	DTMSR-32GDK1% W *SL10G
64GB	DTMSR-64GDK1% C *DLXXG	DTMSR-64GDK1% W *DLXXG
128GB	DTMSR-A28DK1% C *QLXXG	DTMSR-A28DK1% W *QLXXG
256GB	DTMSR-B56DK1% C *QLXXG	DTMSR-B56DK1% W *QLXXG
Note	XXG: 10G-50G % E: Azure Cloud; J: Private Cloud * A: with Wi-Fi antenna; B: with Ethernet daughter board	

© 2020 Innodisk Corporation. All right reserved. Specifications are subject to change without prior notice.



Distributore Autorizzato per l'Italia:

Contradata Milano S.r.l.

Via Solferino 12, 20900 Monza (MB) - Italy

Tel: (+39) 039-230.14.92 | Email: info@contradata.it



www.contradata.it

