


DRPC-W-EHL

- Fanless DIN-Rail Embedded System
- Elkhart Lake Intel® Celeron™ Solution (up to 4 cores)



Features

- Supported CPU:
Intel® Celeron™ J6412 2.0GHz (up to 2.6GHz, quad-core, TDP 10W)
- Support dual independent display
- 2 x 2.5GbE ports
- 1 x M.2 A Key
- 1 x M.2 B Key (with SIM card slot)



External fan module

Specifications

Model Name		DRPC-W-EHL
Chassis	Color	Black
	Dimensions (WxDxH) (mm)	176 x 116 x 60.8
	System Fan	Fanless
	Chassis Construction	Extruded aluminum alloys
Motherboard	CPU	Intel® Celeron® J6412 2.0 GHz (up to 2.6 GHz, quad-core, TDP 10W)
	Chipset	SoC
	Memory	Onboard LPDDR4X 3200MHz 8G (up to 16GB)
Storage	HDD Bay	1 x 2.5" SATA 6Gb/s HDD bay
IO Interfaces	USB	2 x USB 3.2
	LAN	3 x 2.5GbE
	Display	1 x DP 1 x HDMI
	Others	1 x Power button, 1 x Reset button, 1 x Power LED, 1 x HDD LED, 1 x System fan connector
Internal Expansions	RS-232/422/485	2x optional RS-232/422/485 > 2x optionale cable 32005-003500-200
	M.2	1 x M.2 A Key 2230 for WIFI & BT (optional) 1 x M.2 B Key (PCIe x2) 3042 w/SIM slot for 5G (optional)
Power	Power Input	12V DC
	Power Consumption	12V@2.5A (Intel J6412 With 4GB DDR4 Memory)
Reliability	Mounting	DIN-Rail
	Operating Temperature	-20°C ~ 60°C with airflow, 10% ~ 95% non-condensing
	Storage Temperature	-30°C ~ 85°C, 10% ~ 95% non-condensing
	Operating Shock	Half-sine wave shock 5G, 11ms, 3 shocks per axis
	Operating Vibration	MIL-STD-810F 514.5C-2
	Weight (Net/Gross)	0.92/1.16 Kg
	Safety/EMC	CE/FCC
Watchdog Timer	Programmable 1 ~ 255 sec/min	

