

DPM-1210

21.5", Capacitive / Resistive Touch Screen , Industrial Touch Display



Features

- 21.5" LCD Capacitive / Resistive Touch
- Compact structure, IP65 front panel
- All metal structure design, durable
- Support panel and VESA installation



Specifications

Display		Power Specification	
Size	21.5-inch	Power Input	DC 12~24V
Resolution	1920 x 1080	Power Adapter	AC-DC, 12V@5A, 60W
Viewing Angle	89/89/89/89	Power Consumption	19W(Typ.)
Color Support	16.7M	Environmental	
Brightness	250 cd/m ²	Operating Temperature	-10~50°C
Contrast Ratio	3000:1	Storage Temperature	-20~60°C
Response Time	20/5 (Typ.)(Tr/Td) ms	Relative Humidity	10%-90%, @ 40°C (non-condensing)
Backlight	LED	Vibration	5~500Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Backlight Life	40000h	Certifications	CE, FCC
Touch Screen		Mechanical	
Type	Projection Multi Touch Capacitive Touch Screen 5-wire resistive touch screen	Housing	Aluminum alloy panel, all-metal structure
Control Interface	USB	Mounting Method	Panel-mount, VESA-mount
Surface Hardness	≥6H & 3H	Dimension (W x L x H)	528.4x 326.2 x 47.3 mm
Transmittance	85% & 78%	Weight	6.1Kg
I/O Connectors		Packing List	
USB	1 x USB2.0	1 x DPM-1210	
Display	1 x VGA	1 x AC-DC power adapter	
	1 x DVI	1 x USB control cable	
	1 x HDMI/DP	1 x Cable Buckle	
Others	1 x DC-IN (2-Pin Phoenix)	1 x Certificate	
		1 x Warranty Card	
		8 x Panel Mounting Buckles	

Dimensions

